



Rock Dust Hose – MSHA Series 7393

This hose is for rock dust service in underground mines, it is very light, flexible and durable. The cover is flame resistant and the tube is static conductive. The hose also has a helix wire that reduces kinking at sharp bends.
4:1 Design factor

>> Durable and flexible for mine environments

Tube	Black Natural Rubber blend - Static Conductive
Cover	Black Synthetic Rubber blend
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-30°F to +160°F (-34°C to +71°C)
Branding	PARKER SERIES 7393 ROCK DUST HOSE FLAME RESISTANT MSHA NO. IC-123/22 MADE IN USA (MSHA number may vary)
Brand Description	Embossed Brand
Compare to	Goodyear Flextra

LENGTHS: 100 ft. lengths, all sizes, part #'s ending in "2". 50 ft. lengths with soft cuffs, all sizes, part #'s ending "050C".

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7393

Applications

- Dust Suppression and Collection Systems
- Rock Dust Service

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7393-1252	1¼	31.8	2	1.602	40.7	46	2.5	90
7393-1252050C	1¼	31.8	2	1.602	40.7	46	2.5	90
7393-1502	1½	38.1	2	1.834	46.6	52	3.0	90
7393-1502050C	1½	38.1	2	1.834	46.6	52	3.0	90
7393-2002	2	50.8	2	2.362	60.0	79	4.0	75
7393-2002050C	2	50.8	2	2.362	60.0	79	4.0	75
7393-2502	2½	63.5	2	2.862	72.7	97	6.0	60
7393-2502050C	2½	63.5	2	2.862	72.7	97	6.0	60
7393-3002	3	76.2	2	3.409	86.6	132	8.0	50
7393-3002050C	3	76.2	2	3.409	86.6	132	8.0	50