



7244E

## Sand Blast Hose – 4 Ply Series 7244E

Designed for sandblasting of metal castings, steel, stone, cement or wherever abrasive materials are carried at high velocity. The high abrasion resistant, static conducting tube eliminates the need for a static wire.

3:1 Design factor

### >> Highly abrasion resistant and durable

<b>Tube</b>	Black Natural Rubber - Static Conductive
<b>Cover</b>	Black Synthetic Rubber blend
<b>Reinforcement</b>	Multiple textile plies
<b>Temperature Range</b>	-20°F to +160°F (-29°C to +71°C)
<b>Branding</b>	PARKER SERIES 7244E SAND BLAST HOSE 150 PSI WP
<b>Brand Description</b>	Embossed Brand
<b>Compare to</b>	Goodyear Plicord Blast, XF Blast; Kuriyama Sand Blast

**LENGTHS:** 50 ft. special lengths up to 200 ft. available on quotation. Contact IHP Customer Service for details.

**COUPLINGS:** Not offered by Parker – For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in)	OD (mm)	Tube (in.)	Approx. Wt. per 100 Ft.	Max. Rec. WP
7244E-500	½	12.7	2	1.06	26.9	0.21	40	150
7244E-750	¾	19.1	4	1.50	38.1	0.24	65	150
7244E-1000	1	25.4	4	1.89	48.0	0.28	100	150
7244E-1250	1¼	31.8	4	2.17	55.1	0.28	125	150
7244E-1500	1½	38.1	4	2.36	60.0	0.26	130	150
7244E-2000	2	50.8	4	2.87	72.8	0.26	175	150

### Applications

- Sand Blasting