



## DAY-LITE® Suction & Discharge Hose Series 8341

Designed for wet or dry abrasive product transfer service. The highly abrasion resistant tube is also static conductive, eliminating the need for a static wire. The cover is corrugated for flexible handling. This hose is rated for full suction and discharge. 3:1 Design factor

### >> Tube dissipates static for safety

<b>Tube</b>	High Abrasion-Resistant Conductive NR/SBR Blend
<b>Cover</b>	Corrugated Abrasion-Resistant NR/SBR
<b>Reinforcement</b>	Multiple Polyester Spiral Plies plus Helix Wire
<b>Vacuum Rating</b>	Full Suction
<b>Temperature Range</b>	-40°F to +180°F (-40°C to +83°C)
<b>Branding</b>	Parker 8341 Day-Lite Suction and Discharge Hose Made in USA
<b>Brand Description</b>	Tape Brand - Black Letters on Green Stripe
<b>Compare to</b>	Goodyear Plicord Vacuum

**LENGTHS:** 50 and 100 ft.; 1½ in. through 4 in. also available in 200 ft. lengths.  
**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



8341

### Applications

- Sewer Cleaning

Part Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
8341-1500	1½	38.1	2.008	51.0	76.8	4.5	75
8341-2000	2	50.8	2.520	64.0	100.0	6.0	75
8341-3000	3	76.2	3.457	87.8	162.0	9.0	75
8341-4000	4	101.6	4.598	116.8	247.5	12.0	75
8341-6000	6	152.4	6.693	170.0	441.0	18.0	75
8341-8000	8	203.2	8.724	221.0	591.8	24.0	75



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.