



DYNAFLEX®

PVC Standard Duty Suction Hose

Series 7560

This is a flexible hose that will withstand full suction and discharge pressure. It will handle a variety of liquid and solid materials such as water, slurry transfer, sewage, air, chemicals, grains and pellets. A versatile hose for agriculture, mining, construction and industry.

3:1 Design factor

>> Designed for full suction and discharge service

Tube	Green PVC – Smooth
Cover	Green PVC – Smooth
Reinforcement	Rigid white PVC helix
Temperature Range	-5°F to +140°F (-21°C to +60°C)
Branding	None
Compare to	Gates 100 GR; Kanaflex 100 GR; Kuriyama G and J; Pacific Echo 110, 113; Petzetakis 12500; Superflex 1000 GR

LENGTHS: 100 ft. coils ¾ in. through 6 in.; 20, 25 and 30 ft. straight lengths for 8 in. ID.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Aprox. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7560-750	¾	19.1	1.00	25.0	20	3.5	120
7560-1000	1	25.4	1.24	31.5	25	4.5	120
7560-1250	1¼	31.8	1.53	38.9	32	5.7	120
7560-1500	1½	38.1	1.78	45.2	39	6.7	100
7560-2000	2	50.8	2.32	58.9	57	9.0	95
7560-2500	2½	63.5	2.81	71.4	80	11.0	75
7560-3000	3	76.2	3.43	87.1	105	14.0	65
7560-4000	4	101.6	4.45	113.0	164	18.0	55
7560-6000	6	152.4	6.60	167.6	308	30.0	40
7560-8000	8	203.2	8.80	223.5	507	39.0	35

7560

Applications

- Mining
- Sewage
- Slurry Transfer