



DYNAFLEX® All Clear PVC Suction Hose – FDA Series 7563

Heavy duty food grade material handling hose complies with all applicable FDA specifications. Smooth tube construction is excellent for transferring powder, pellets, or other dry materials without build-up. Clear PVC construction permits visual observation of materials being conveyed. Complies with FDA CFR Title 21 parts 170-199.

3:1 Design factor

>> Smooth tube prevents blockage

Tube	Clear PVC – Smooth
Cover	Clear PVC – Corrugated
Reinforcement	Rigid clear PVC helix
Temperature Range	-5°F to +140°F (-21°C to +60°C)
Branding	None
Compare to	Gates 201 CR; Goodyear Nutriflex; Jason 4660; Kanaflex 200 SFG; Kuriyama WT; Pacific Echo 145; Petzetakis 12426SE; Superflex 9000

LENGTHS: 100 ft. coils

COUPLINGS: For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7563

Applications

- Bulk Food Transfer

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7563-1000	1	25.4	1.22	31.0	17	2.0	55
7563-1250	1¼	31.8	1.48	37.6	21	3.0	50
7563-1500	1½	38.1	1.84	46.7	34	3.0	50
7563-2000	2	50.8	2.36	59.9	50	4.0	40
7563-2500	2½	63.5	2.87	72.9	68	5.0	40
7563-3000	3	76.2	3.50	88.9	100	6.0	40
7563-4000	4	101.6	4.64	117.9	152	8.0	35
7563-6000	6	152.4	6.50	165.1	300	12.0	30