



FLEX-EVER™ 2000 Gasoline Pump Hose – UL330/ULC Series 7280

IMPORTANT: REFER TO THE SAFETY AND TECHNICAL DATA INFORMATION SECTION FOR THE PROPER USE OF THIS HOSE.

Parker's premium gasoline dispenser hose. The dual helical wires of the heavy duty hardwall construction eliminate meter creep and helps prevent kinking. The Hypalon cover provides excellent ozone and abrasion resistance, resulting in longer service life. For use with gasohol blend, diesel, leaded, unleaded and oxygenated gasoline products. All assemblies are pressure and electrical conductivity tested per UL330 specifications. Blue, Green, Red and Yellow covers available on quotation.

4:1 Design factor

**>> Kink resistant and durable;
offered as UL approved assemblies**

| | |
|--------------------------|--|
| Tube | Black Nitrile |
| Cover | Black Hypalon |
| Reinforcement | Multiple textile braids with dual helix wire |
| Vacuum Rating | Full Suction |
| Temperature Range | -40°F to +180°F (-40°C to +82°C) |
| Branding | PARKER SERIES 7280 FLEX-EVER™ 2000 GASOLINE HOSE (UL) LISTED 655N MH530 (ULC) MADE IN USA B5 (DATE CODE) PN16 TRbF131T.2 |
| Brand Description | Ink Brand - White letter color |

LENGTHS: Nominal 500 ft. reels. Max. of 5 pieces with 50 ft. min. lengths.

COUPLINGS: Only assemblies are available from Parker – no individual coupling sales.

7280

Applications

- Gas Station
- Oil Transfer

| Part No. | ID (in.) | ID (mm) | Reinf. Braids | OD (in.) | OD (mm) | Approx. Wt. per 100 Ft. | Min. Bend Radius | Max. Rec. WP |
|------------|----------|---------|---------------|----------|---------|-------------------------|------------------|--------------|
| 7280-632A | 5/8 | 15.9 | 2 | 1.031 | 26.2 | 38 | 3.0 | 150 |
| 7280-752A | 3/4 | 19.1 | 2 | 1.172 | 29.8 | 45 | 4.0 | 150 |
| 7280-1002A | 1 | 25.4 | 2 | 1.453 | 36.9 | 60 | 5.0 | 150 |