

## SOFT-FLEX® 2000 Marine Refueling Hose – Green Cover Series 7114GRM

**IMPORTANT: REFER TO THE SAFETY AND TECHNICAL DATA INFORMATION SECTION FOR THE PROPER USE OF THIS HOSE.**

Parker's UL Listed series 7114GRM marine refueling hose is a green non-marking cover, 4-ply spiral reinforced softwall hose, which includes a static grounding wire for electrical continuity. This extremely flexible hose can be used with various marina fuels such as unleaded gasoline, alcohol blended fuel and various diesel fuels.

4:1 Design factor

### >> Abrasion and kink resistant

Tube	Nitrile
Cover	Green Nitrile/PVC
Reinforcement	Multiple textile plies with static wire
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	PARKER SERIES 7114 SOFT-FLEX 2000 MARINE REFUELING HOSE 4SP UL LISTED 655N MH530 MADE IN USE (date code)
Brand Description	Ink Brand - White letters
Compare to	Goodyear BC Marina; Thermoid Pumpflex Softwall Marina

**LENGTHS:** ¾ in. – 400 ft.; 1 in. – 300 ft.; both 1-piece continuous length reels

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7651. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7114-754GRM	¾	19.1	4	1.100	27.9	32	6.0	150
7114-1004GRM	1	25.4	4	1.360	34.5	42	8.0	150



7114GRM

### Applications

- Marine Refueling