



SOFT-FLEX® 2000 Gasoline Pump Hose – UL330/ULC Series 7114

IMPORTANT: REFER TO THE SAFETY AND TECHNICAL DATA INFORMATION SECTION FOR THE PROPER USE OF THIS HOSE.

SOFT-FLEX 2000 hose is a quality softwall gasoline pump hose used in applications that do not require hardwall hose. The multiple spiral reinforcement provides increased strength over one or two-braid hose without sacrificing flexibility or ease of handling. The Hypalon cover is highly resistant to cuts, abrasion, sun and weather, and will not scratch or mark vehicle finish. SOFT-FLEX 2000 hose is for use with diesel, leaded, unleaded and oxygenated gasoline products.

4:1 Design factor

>> Lightweight and flexible for easy handling

Tube	Black Nitrile
Cover	Black Hypalon
Reinforcement	Multiple textile spirals with static wire
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	PARKER SERIES 7114 SOFT-FLEX® 2000 GASOLINE HOSE 4SP UL LISTED 655N MH530 MADE IN USA (DATE CODE)
Brand Description	Ink Brand - White letter color
Compare to	Goodyear Pacer; Thermoid Pumpflex I Softwall

LENGTHS: Random lengths on reels in cartons: 5/8" = 475 ft.; 3/4" = 350 ft.; 1" = 250 ft. 3 pieces max. and 50 ft. min. lengths.

COUPLINGS: Only assemblies are available from Parker – no individual coupling sales.

7114

Applications

- Gas Station
- Oil Transfer

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7114-63154A	5/8	15.9	4	0.960	24.4	26	5.0	150
7114-75154A	3/4	19.1	4	1.100	27.9	32	6.0	150
7114-100154A	1	25.4	4	1.360	34.5	42	8.0	150