



SUPER-FLEX® 2000 Gasoline Pump Hose – UL330/ULC Series 7124

IMPORTANT: REFER TO THE SAFETY AND TECHNICAL DATA INFORMATION SECTION FOR THE PROPER USE OF THIS HOSE.

SUPER-FLEX 2000 is a high quality wire braid hose for use anywhere a hardwall hose is required. The single wire braid construction provides static conductivity, increased hose strength, resistance to crushing, and a long service life. The SUPER-FLEX 2000 is usable on reeling devices or applications where retractable cables are required to handle diesel, leaded, unleaded, and oxygenated gasoline products. The Hypalon cover is highly resistant to cuts, abrasion, sun, weather, and will not scratch or mark vehicle finish.

4:1 Design factor

>> Hardwall construction for long service life

Tube	Black Nitrile
Cover	Black Hypalon
Reinforcement	One wire braid
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	PARKER USA 7124 SUPER-FLEX® 2000 GASOLINE HOSE (UL) LISTED 655NMH530 (DATE CODE)
Brand Description	Ink Brand - White letter color
Compare to	Thermoid Pumpflex II Hardwall; Goodyear Flexsteel Hardwall

LENGTHS: Nominal 500 ft. reels. Max. of 5 pieces with 50 ft. min. lengths.

COUPLINGS: Only assemblies are available from Parker - no individual coupling sales.

7124

Applications

- Gas Station
- Oil Transfer

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7124-631A	5/8	15.9	1	0.969	24.6	34	3.0	150
7124-751A	3/4	19.1	1	1.090	27.7	39	4.0	150
7124-1001A	1	25.4	1	1.340	34.0	49	5.0	150