



TRANSLITE® Tank Truck Hose

Series 7216 (Black) / 7217 (Red)

A lightweight and flexible hose used in the transfer of gasoline, alcohol blended fuels, diesel fuels and other petroleum products. The hose is designed for full suction and discharge applications.


4:1 Design factor

>> Abrasion resistant for long service life

Tube	Black Nitrile
Cover	Black or Red Neoprene
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-20°F to +180°F (-29°C to +82°C)
Branding	PARKER SERIES 7216 TRANSLITE® TANK TRUCK HOSE XXX PSI MAX WP MADE IN USA 001
Brand Description	Tape Brand: Black letters on orange stripe - 7216 Red letters on white stripe - 7217
Compare to	Goodyear Plicord Flexwing Petroleum; Gates Longhorn; Boston Puma; Titan SW303/309

LENGTHS: 100 ft.; 8", 50 ft. Lengths of up to 200 ft. available on quotation. Contact IHP Customer Service for details.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-1002	1	25.4	2	1.364	34.6	46	2.0	150
-1252	1¼	31.8	2	1.670	42.4	65	3.0	150
-1502	1½	38.1	2	1.960	49.8	92	4.0	150
-2002	2	50.8	2	2.512	63.8	120	6.0	150
-2502	2½	63.5	2	3.028	76.9	155	9.0	150
-3002	3	76.2	2	3.552	90.2	198	12.0	150
-4002	4	102.0	2	4.626	117.5	360	16.0	150
-5004	5	127.0	4	5.748	146.0	487	39.0	100
-6004	6	152.4	4	6.772	172.0	546	48.0	75
-8004	8	203.2	4	8.888	225.8	812	72.0	75

Applications

- Petroleum Transfer



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.



WARNING! Not to be submersed in marine applications.