



7216E

TRANSLITE® Tank Truck Hose – Equalizer Version Series 7216E

A lightweight and flexible hose used in the transfer of gasoline, alcohol blended fuels, diesel fuels and other petroleum products. The hose is designed for full suction and discharge applications.

3:1 Design factor

>> Economical

Tube	Black Nitrile
Cover	Black Neoprene
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-20°F to +160°F (-29°C to +71°C)
Branding	PARKER SERIES 7216E TANK TRUCK HOSE XXX PSI MAX WP
Brand Description	Tape Brand - orange stripe with black letters
Compare to	Kuriyama T605AA; Goodyear Plicord Flexwing Petroleum; Gates Longhorn; Boston Puma

LENGTHS: 100 ft. coils

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7216E-1002	1	25.4	2	1.28	34.6	47	3.0	150
7216E-1252	1¼	31.8	2	1.69	42.4	65	4.0	150
7216E-1502	1½	38.1	2	2.00	49.8	92	5.0	150
7216E-2002	2	50.8	2	2.50	63.8	110	6.0	150
7216E-2502	2½	63.5	2	3.00	76.9	155	7.0	150
7216E-3002	3	76.2	2	3.62	90.2	210	8.0	150
7216E-4002	4	102.0	2	4.65	117.5	280	11.0	150

Applications

- Petroleum Transfer



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.



WARNING! Not to be submersed in marine applications.