

## Heavy Duty Fuel Suction and Discharge Hose Series 7330

Designed for heavy duty service in the transfer of petroleum products including gasoline, oil, and diesel fuels. The hose is designed for suction and discharge applications.  
4:1 Design factor

### >> Designed for durability

<b>Tube</b>	Black Nitrile
<b>Cover</b>	Black Neoprene
<b>Reinforcement</b>	Multiple textile plies with helix wire
<b>Temperature Range</b>	-20°F to +180°F (-29°C to +82°C)
<b>Branding</b>	PARKER SERIES 7330 HD TANK TRUCK XXX PSI MAX WP MADE IN USA 001
<b>Brand Description</b>	Tape Brand - Red letters on white stripe
<b>Compare to</b>	Titan SW353; Goodyear Plicord Super Black Flexwing

**LENGTHS:** 100 ft. Lengths up to 200 ft. continuous on quotation.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7330-1250	1¼	31.8	2	1.686	42.8	71	6.0	300
7330-1500	1½	38.0	2	1.976	50.2	100	8.0	300
7330-2000	2	50.8	4	2.622	66.6	166	8.0	300
7330-3000	3	76.2	4	3.654	92.8	241	15.0	300
7330-4000	4	101.6	4	4.812	122.2	387	20.0	300
7330-6000	6	152.4	4	6.906	175.4	665	36.0	300
7330-8000	8	203.2	6	9.118	231.6	1157	48.0	300

7330

### Applications

- Fuel Suction and Discharge
- Unloading Barges