



Transport Fuel Discharge Hose – Softwall

Series 7224 (Red) / 7225 (Black)

This hose is used in truck-mounted transport service applications, which include discharge of gasoline, oil and fueling of diesel locomotives, buses and trucks.


4:1 Design factor

>> Flexible for ease of use and handling

Tube	Black Nitrile
Cover	Red or Black Neoprene
Reinforcement	Multiple textile plies with static wire
Temperature Range	-20°F to +180°F (-29°C to +82°C)
Branding	7224 PARKER SERIES 7224 FUEL DISCHARGE 200 PSI MAX WP MADE IN USA 001 7225 PARKER SERIES 7225 FUEL DISCHARGE 200 PSI MAX WP MADE IN USA 001
Brand Description	7224 - Tape Brand - Red letters on black stripe 7225 - Tape Brand - Black letters on red stripe
Compare to	Gates Steer; Titan SS242; Goodyear Plicord Fuel Discharge

LENGTHS: 100 ft. Lengths up to 200 ft. on quotation. Contact IHP Customer Service for details.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-1500	1½	38.1	2	2.000	50.8	84	9.0	200
-2000	2	50.8	2	2.504	63.6	108	11.0	200
-3000	3	76.2	2	3.504	89.0	161	12.0	200
-4000	4	101.6	2	4.536	115.2	209	20.0	200

Applications

- Fuel and Oil Delivery



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.