



Heavy Duty Fuel Discharge Hose

Series 7351

Softwall petroleum transfer hose for heavy duty service. The high grade nitrile tube will handle gasoline, oil and diesel fuel. The high grade Neoprene cover is resistant to weather, oil and abrasion.

4:1 Design factor

>> Weather resistant to withstand the elements

Tube	Black Nitrile
Cover	Black Neoprene
Reinforcement	Multiple textile plies with static wire
Temperature Range	-22°F to +180°F (-30°C to +82°C)
Branding	PARKER SERIES 7351 FUEL DISCHARGE HOSE XXX PSI MAX WP MADE IN USA 001
Brand Description	Tape Brand - White letters on red stripe
Compare to	Titan SW353

LENGTHS: 100 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7351-2000	2	50.8	4	2.716	69.0	170	24.0	200
7351-3000	3	76.2	4	3.780	96.0	262	36.0	200
7351-4000	4	102.0	4	4.772	121.2	320	48.0	200
7351-6000	6	152.4	4	6.812	173.0	501	72.0	150
7351-8000	8	203.2	4	8.646	219.6	500	96.0	150

7351

Applications

- Fuel Transport