



SAE 30R7 Fuel Line and Vapor Emission Hose

Gasoline and Vapor Emission Hose manufactured to meet SAE 30R7 specifications. Durable cover resists deterioration from oil, grease, heat and ozone and gives long service life.

4:1 Design factor

>> Designed for long service life

Tube	Black NBR
Cover	Black Neoprene
Reinforcement	Textile Spirals
Temperature Range	-30°F to +250°F (-34°C to +121°C)
Branding	3/16 in. ID FUEL/VAPOR LINE SAE30R7 (DATE CODE)
Brand Description	Ink Brand - White letter color
Compare to	Thermoid Fueling, Vapor Emission and Crankcase Ventilation SAE 30R7

LENGTHS: 250 ft. per spool, max. 2 pieces. No piece shorter than 25 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Layers	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
39553	3/16	4.8	2	0.406	10.3	7	2.0	75
39550	1/4	6.4	2	0.500	12.7	10	2.0	50
39551	5/16	7.9	2	0.563	14.3	11	3.0	50
39552	3/8	9.5	2	0.625	15.9	14	3.5	50

3955x

Applications

- Carburetor Fuel Line