



## BS & W™ Oilfield Suction Hose

### Series 7208 - Smooth Cover

**CAUTION:** Not to be used for refined petroleum products

An economical, lightweight, and flexible hose designed for the transfer of crude oil and brine water. Specially designed for oilfield waste pit recovery service. Smooth cover.

4:1 Design factor

### >> Rugged construction for extreme conditions

<b>Tube</b>	Special black synthetic rubber compound
<b>Cover</b>	Special black synthetic rubber compound
<b>Reinforcement</b>	Textile plies with helix wire
<b>Temperature Range</b>	-30°F to +180°F (-34°C to +82°C)
<b>Branding</b>	PARKER SERIES 7208 BS&W OIL FIELD SUCTION HOSE NOT FOR REFINED FUELS MADE IN USA 001
<b>Brand Description</b>	Tape Brand - White letters on blue stripe
<b>Compare to</b>	Goodyear Flexwire Oilfield

**LENGTHS:** 100 ft. lengths of up to 200 ft. available on quotation. Contact IHP Customer Service for details.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7208

### Applications

- Oil Field Waste Recovery

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Aprox. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7208-1000	1	25.4	2	1.408	35.8	48	2.0	150
7208-1250	1¼	31.8	2	1.688	42.9	67	3.0	150
7208-1500	1½	38.1	2	2.000	50.8	98	4.0	150
7208-2000	2	50.8	2	2.512	63.8	125	6.0	150
7208-2500	2½	63.5	2	3.000	76.2	155	9.0	150
7208-3000	3	76.2	2	3.512	89.2	195	12.0	150
7208-4000	4	102.0	2	4.552	115.6	260	16.0	150
7208-6000	6	152.4	4	6.716	170.6	515	48.0	150



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly which is less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.