



BS & W™ Oilfield Suction Hose – Premium Version Series 7213 - Corrugated Cover

CAUTION: Not to be used for refined petroleum products

An economical, lightweight and flexible hose designed for the transfer of crude oil and brine water. Specially designed for oilfield waste pit recovery service. Corrugated for flexibility.

4:1 Design factor

>> Corrugated cover for increased flexibility and ease of handling

Tube	Special black synthetic rubber compound
Cover	Special black synthetic rubber compound
Reinforcement	Textile plies with helix wire
Temperature Range	-30°F to +180°F (-34°C to +82°C)
Branding	PARKER SERIES 7213 BS&W OIL FIELD SUCTION HOSE NOT FOR REFINED FUELS MADE IN USA 001
Brand Description	Tape Brand - White letters on blue stripe
Compare to	Goodyear Flextra Oilfield; Kuriyama T601AA; Jason Tupelo 4677; Texcel Tex-Vac

LENGTHS: 100 ft. lengths of up to 200 ft. available on quotation. Contact IHP Customer Service for details.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7213

Applications

- Oil Field Waste Recovery

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7213-1500	1½	38.1	2	1.976	50.2	86	4.0	150
7213-2000	2	50.8	3	2.520	64.0	121	6.0	150
7213-2500	2½	63.5	3	3.020	76.7	147	9.0	150
7213-3000	3	76.2	3	3.520	89.4	174	12.0	150
7213-4000	4	101.6	3	4.568	116.0	258	16.0	150
7213-6000	6	152.4	5	6.748	171.4	474	48.0	150



WARNING! Combination nipple and bands reduce the working pressure of the assembly which is less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.