



WILDCATTER® XT

Slim Hole Rotary Drill Hose

Series 7234

Designed for rotary service on portable drilling units, workover rigs and seismograph equipment. This tough, flexible and versatile hose can also be used as a discharge hose for reverse circulation, acidizer and cement solution. Meets API-7 requirements. 2.5:1 Minimum design factor

>> Rugged construction eliminates down time

Tube	Black Neoprene
Cover	Black Hypalon with blue stripe
Reinforcement	Multiple wire spirals
Temperature Range	-40°F to +200°F (-40°C to +93°C)
Branding	PARKER USA WILDCATTER® 3000 PSI WP 001
Brand Description	Tape Brand - Black letter color, blue background
Compare to	Gates Powerbraid Plus Slim Rotary Hole

LENGTHS: 50 ft. and 100 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7234-2002XT	2	50.8	4	2.590	65.8	275	18.0	3000

7234

Applications

- Portable Drilling Units
- Workover Rigs