



Frac Tank Suction and Discharge Hose

Series 7307

Designed for various oilfield suction and Frac tank service applications including drilling mud, crude oil, salt and fresh water and dilute hydrochloric acid. Oil resistant tube and cover. **Not recommended for refined fuels.**

3:1 Design factor

>> Corrugated cover provides superior flexibility

Tube	Black Nitrile/SBR Blend
Cover	Black Nitrile/SBR Blend – Corrugated
Reinforcement	Multiple polyester textile plies
Temperature Range	-20°F to +180°F (-28°C to +82°C)
Branding	PARKER SERIES 7307 OILFIELD SUCTION & FRAC TANK HOSE 100 PSI NOT FOR REFINED FUELS MADE IN USA
Brand Description	Tape Brand - Yellow letters on blue stripe
Compare to	Texcel Super Frac

LENGTHS: 100 ft.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7307-4000	4	101.6	2	4.590	116.6	251	12.0	150
7307-6000	6	152.4	3	6.713	170.5	458	18.0	150
7307-8000	8	203.2	3	8.800	223.5	658	24.0	150

7307

Applications

- Frac Tank Loading and Unloading