



## WILDCATTER®

### Hot Oiler Hose

#### Series 7301

A unique hot oiler hose specially designed for transferring hot oil at 275° F continuous, 300° F intermittent. The rugged neoprene cover is abrasion and gouge resistant.

3:1 Design factor

#### >> Long lasting and durable

Tube	Black Neoprene
Cover	Black Neoprene
Reinforcement	Multiple wire braids
Temperature Range	-40°F to +275°/300°F (-40°C to +135°/149°C)
Branding	PARKER USA 7301 WILDCATTER HOT OILER HOSE 1-1/2 ID 2250 PSI MAX WP TEMP RATING 275° F CONTINUOUS 300° F INTERMITTENT 001
Brand Description	Tape Brand - Red letter color
Compare to	Titan SW387

**LENGTHS:** 50 ft. and 75 ft. available

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7301-1502	1½	38.1	2	2.000	50.8	159	13.0	2250
7301-150275	1½	38.1	2	2.000	50.8	159	13.0	2250

7301

### Applications

- Hot Oil Transfer