

## Mud Hose - 300 PSI

## Series 7309

Designed for use as a high pressure discharge hose for drilling mud, petroleum waste and water discharge applications. The tube is rated for RMA Class A-High Oil Resistance.

4:1 Design factor

## >> Rugged construction with oil resistant cover

Tube	Black Nitrile				
Cover	Black Neoprene				
Reinforcement	Multiple polyester textile plies with static wire				
Temperature Range	-20°F to +180°F (-28°C to +82°C)				
Branding	PARKER SERIES 7309 MUD HOSE 300 PSI MAX WP MADE IN USA				
<b>Brand Description</b>	Tape Brand - Black letters on yellow stripe				
Compare to	Titan SS-145 Oil and Gas Hose, SS-160 Mud Hose				

LENGTHS: 100 ft. standard. Lengths up to 200 ft. on quotation. Contact IHP Customer Service for details.

Part No.	ID (in.)	ID (mm)	Reinf. Layers	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7309-2000	2	50.8	4	2.764	70.2	475	24.0	300
7309-3000	3	76.2	4	3.835	97.4	267	36.0	300
7309-4000	4	101.6	4	4.898	124.4	358	48.0	300
7309-5000	5	127.0	4	5.937	150.8	461	60.0	300
7309-6000	6	152.4	6	7.087	180.0	628	72.0	300
7309-8000	8	203.2	6	9.250	233.2	884	96.0	300

7309

## **Applications**

- Petroleum Waste
- Mud Drilling
- High Pressure Water