

Conduit Hose – Reinforced – US MSHA Series 7337M (Smooth Cover) / 7337 (Wrapped Cover)

Designed for use as cable cover on underground mining equipment. Meets US MSHA standards for flame resistance and wall thickness and is embossed with US MSHA legend.

>> Rugged construction for extreme conditions

Tube	Black Synthetic Rubber
Cover	Black Synthetic Rubber 7337M Smooth Cover 7337 Mandrel-built Wrapped Cover
Reinforcement	Multiple textile plies
Temperature Range	-30°F to +180°F (-34°C to +82°C)
Branding	PARKER SERIES 7337 PREMIUM CONDUIT HOSE FLAME RESISTANT MINE CONDUIT MSHA NO. 2G-2/11 MADE IN USA (7337) MSHA NO. 18-HCA060001 MADE IN USA (7337M)
Brand Description	Embossed Brand

LENGTHS: 7337: 50 ft. 100 ft. and 200 ft. are stocked in some sizes.

7337M: Reels packaged with standard lengths as minimum, with up to one 50 ft. length max. over standard. 1½" reel packaged with 150 ft. as minimum, up to the standard length as maximum.

Sizes ½" through 1": 90% 1-piece reels, 10% 2-piece with 50 ft. multiples.

Sizes 1½" through 1½": 70% 1-piece reels, 30% 2-piece with 50 ft. multiples.

COUPLINGS: None required

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.
7337M-502	½	12.7	2	0.968	24.6	31
7337M-632	⅝	15.9	2	1.093	27.8	37
7337M-752	¾	19.1	2	1.218	30.9	41
7337M-1002	1	25.4	2	1.468	37.3	52
7337M-1132	1⅛	28.6	2	1.593	40.5	57
7337M-1252	1¼	31.8	2	1.718	43.6	63

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.
7337-1382	1⅝	34.9	2	1.811	46.0	69
7337M-1502	1½	38.1	2	1.929	49.0	73
7337-1752	1¾	44.5	2	2.183	55.4	85
7337-1882	1⅞	47.6	2	2.308	58.6	90
7337-2002	2	50.8	2	2.435	61.8	96
7337-2252	2¼	57.2	2	2.687	68.2	107
7337-2382	2⅝	60.3	2	2.809	71.3	112
7337-2502	2½	63.5	2	2.933	74.5	117
7337-3002	3	76.2	2	3.435	87.2	139
7337-3502	3½	90.0	2	3.976	101.0	162
7337-4002	4	102.0	2	4.449	113.0	182
7337-5002	5	127.0	2	5.433	138.0	225
7337-6002	6	152.4	2	6.437	163.5	271



7337

Applications

- Underground Mines