



## Conduit Hose – Non-Reinforced – US MSHA Series 7338

Designed for use as cable cover on underground mining equipment. Meets US MSHA standards for flame resistance and wall thickness and is embossed with US MSHA legend.

### >> Economical option without reinforcement

<b>Construction</b>	Minimum 3/16 in. thick Black Synthetic Rubber tubing
<b>Temperature Range</b>	-30°F to +180°F (-34°C to +82°C)
<b>Branding</b>	PARKER SERIES 7338 PREMIUM CONDUIT HOSE FLAME RESISTANT MINE CONDUIT MSHA NO. 2G-57/4 MADE IN USA (USMSHA number may vary)
<b>Brand Description</b>	Embossed Brand
<b>Compare to</b>	Goodyear M&P Mine Conduit

**LENGTHS:** 50 ft. Many sizes also stocked in 100 ft. and 200 ft. lengths

**COUPLINGS:** None required

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.
7338-1750	1¼	44.5	2.175	55.2	87
7338-2000	2	50.8	2.427	61.6	98
7338-2250	2¼	57.2	2.679	68.0	110
7338-2380	2¾	60.3	2.801	71.1	115
7338-2500	2½	63.5	2.927	74.3	121
7338-3000	3	76.2	3.428	87.1	143

7338

### Applications

- Underground Mines