



SUPER-FLEX® Water Suction Hose Series 7392

This water suction hose is designed to handle a wide range of applications in industry, construction and agriculture. The tough, flexible EPDM rubber construction will resist abrasion, weathering and the effects of agricultural herbicides and other mild chemicals. Incorporates a steel wire helix in the hose wall for full suction capabilities, as well as high tensile tire cord fabric for discharge pressure.

4:1 Design factor

>> Weather resistant

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-40°F to +212°F (-40°C to +100°C)
Branding	PARKER SERIES 7392 WATER SUCTION & DISCHARGE MADE IN USA
Brand Description	Embossed Brand
Compare to	Goodyear Plicord Con-Ag Water S&D; Gates Barracuda; Titan SW300

LENGTHS: 100 ft. sizes through 6 in. ID; 50 ft. sizes 8 in. - 12 in.; 20 ft. also available sizes 6 in. - 12 in.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7392

Applications

- Construction
- Agriculture

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7392-1500	1½	38.1	2	1.904	48.36	83	6.0	150
7392-2000	2	50.8	2	2.449	62.20	117	7.0	150
7392-2500	2½	63.5	2	2.956	75.08	155	8.0	150
7392-3000	3	76.2	2	3.504	89.00	200	10.0	150
7392-4000	4	107.0	2	4.528	115.01	315	14.0	150
7392-5000	5	127.0	2	5.656	143.67	500	22.0	100
7392-6000	6	152.4	4	6.842	173.79	618	30.0	100
7392-8000	8	203.2	4	8.866	225.20	846	38.0	100
7392-10000	10	254.0	4	10.938	277.81	1119	50.0	100
7392-12000	12	304.8	4	13.080	332.23	1510	66.0	100



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.