



SUPER-FLEX® Water Suction Hose – Equalizer Version Series 7392E

This economic water suction hose is designed to handle a wide range of applications in industry, construction and agriculture. The tough, flexible EPDM rubber construction will resist abrasion, weathering and the effects of agricultural herbicides and other mild chemicals. Incorporates a steel wire helix in the hose wall for full suction capabilities, as well as high tensile tire cord fabric for discharge pressure. 3:1 Design factor

>> Economical, long lasting

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Multiple textile plies with helix wire
Temperature Range	-20°F to +180°F (-29°C to +82°C)
Branding	PARKER SERIES 7392E WATER SUCTION HOSE – XXX PSI MAX WP
Brand Description	Tape Brand - Blue stripe with white letters
Compare to	Goodyear Plicord Con-Ag Water S&D; Titan SW300; Gates Barracuda

LENGTHS: 100 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7392E-1500	1½	38.1	2	1.95	49.53	85	5.0	150
7392E-2000	2	50.8	2	2.48	62.99	110	7.0	150
7392E-2500	2½	63.5	2	3.00	76.20	160	9.0	150
7392E-3000	3	76.2	2	3.50	88.90	180	10.5	150
7392E-4000	4	107.0	2	4.60	116.84	290	16.0	100
7392E-6000	6	152.4	2	6.75	171.40	560	30.0	100

7392E

Applications

- Construction
- Agriculture



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.