



SUPER-FLEX® Heavy Duty Water Suction Hose Series 7325

This hose is designed for heavy-duty applications requiring endurance and higher pressure ratings. The hose is also designed to make tight bends without kinking. The tough, flexible EPDM synthetic rubber provides resistance to abrasion, weathering and many industrial and agricultural chemicals.
4:1 Design factor

>> Weatherproof for exposure to the elements

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Textile plies with helix wire
Temperature Range	-40°F to +212°F (-40°C to +100°C)
Branding	PARKER SERIES 7325 HD WATER SUCTION 300 PSI MAX WP MADE IN USA
Brand Description	Tape Brand - White letters on blue stripe
Compare to	Titan EW301; Goodyear Versiflo 100

LENGTHS: 100 ft. and 200 ft. lengths.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7325-1500	1½	38.1	4	2.094	53.2	122	6.0	300
7325-2000	2	50.8	4	2.648	67.3	171	8.0	300
7325-2500	2½	63.5	4	3.192	81.1	228	10.0	300
7325-3000	3	76.2	4	3.700	94.0	270	12.0	300

7325

Applications

- Irrigation
- Surface Mining



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.