



DYNAFLEX®

PVC Standard Duty Suction Hose

Series 7560

This is a flexible hose that will withstand full suction and discharge pressure. It will handle a variety of liquid and solid materials such as water, slurry, sewage, air, chemicals, grains and pellets. A versatile hose for agriculture, mining, construction and industry.

3:1 Design factor

>> Designed for full suction and discharge service

Tube	Green PVC–Smooth
Cover	Green PVC–Smooth
Reinforcement	Rigid white PVC helix
Temperature Range	-5°F to +140°F (-21°C to +60°C)
Branding	None
Compare to	Gates 100 GR; Kanaflex 110 GR; Kuriyama G and J; Pacific Echo 110, 113; Petzetakis 12500; Superflex 1000 GR

LENGTHS: 100 ft. coils ¾ in. through 6 in.; 20, 25 and 30 ft. straight lengths for 8 in.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7560

Applications

- Agriculture
- Mining
- Construction
- Industry

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Aprox. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7560-750	¾	19.1	1.00	25.0	20	3.5	120
7560-1000	1	25.4	1.24	31.5	25	4.5	120
7560-1250	1¼	31.8	1.53	38.9	32	5.7	120
7560-1500	1½	38.1	1.78	45.2	39	6.7	100
7560-2000	2	50.8	2.32	58.9	57	9.0	95
7560-2500	2½	63.5	2.81	71.4	80	11.0	75
7560-3000	3	76.2	3.43	87.1	105	14.0	65
7560-4000	4	101.6	4.45	113.0	164	18.0	55
7560-6000	6	152.4	6.60	167.6	308	30.0	40
7560-8000	8	203.2	8.80	223.5	507	39.0	35