



DYNAFLEX® Multi-Purpose PVC Suction Hose Series 7561

Extremely lightweight and flexible for general service, low pressure applications. Will handle both full suction and discharge pressure, and smooth bore design allows unrestricted flow.

3:1 Design factor


>> Lighter weight with greater flexibility

Tube	Green PVC – Smooth
Cover	Green PVC – Corrugated
Reinforcement	Rigid white PVC spiral helix
Temperature Range	-5°F to +140°F (-21°C to +60°C)
Branding	None
Compare to	Kanaflex 112 CL; Kuriyama WG; Pacific Echo 120; Superflex TX

LENGTHS: 100 ft. coils.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP @68°F	Max. Rec. WP @140°F
7561-1500	1½	38.1	1.78	45.2	33	5	80	25
7561-2000	2	50.8	2.32	58.9	46	7	65	20
7561-2500	2½	63.5	2.83	63.8	60	9	60	20
7561-3000	3	76.2	3.40	86.4	75	12	45	15
7561-4000	4	102.0	4.45	113.0	132	15	40	13



7561

Applications

- Water Suction
- Slurries