



DYNAFLEX®

Medium Duty PVC Clear Suction Hose – FDA Series 7564

Rugged, medium duty general purpose PVC suction and transfer hose for the agricultural, construction, mining and general industrial markets. Smooth tube ensures full flow.

3:1 Design Factor.

>> Smooth tube ensures full flow

Tube	Clear PVC – Smooth
Cover	Clear PVC – Smooth
Reinforcement	Rigid white PVC helix
Temperature Range	-5°F to +140°F (-21°C to +60°C)
Branding	None
Compare to	Gates 101 CL, 200 CL; Goodyear Nutriflow; Jason 4606; Kuriyama H; Pacific Echo 090, 115; Superflex 1000CL

LENGTHS: 100 ft. coils

COUPLINGS: For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7564-500	½	12.7	0.75	19.0	12	2.5	120
7564-750	¾	19.1	1.00	25.4	20	3.0	90
7564-1000	1	25.4	1.22	31.0	26	4.0	90
7564-1250	1¼	31.8	1.53	38.9	37	5.0	80
7564-1500	1½	38.1	1.81	46.0	44	6.0	75
7564-2000	2	50.8	2.34	59.4	67	8.0	75
7564-2500	2½	63.5	2.85	72.4	90	10.0	75
7564-3000	3	76.2	3.45	87.6	114	12.0	65
7564-4000	4	101.6	4.50	114.3	181	16.0	55
7564-6000	6	152.4	6.65	168.9	336	24.0	35



7564

Applications

- Mining
- Transfer of Bulk Food Products
- Marine water and baitwell