



## Water Discharge Hose – Equalizer Series Series 7306E

Remarkably lightweight for easy handling, with the flexibility of a rubber tube and cover. Economical for short term or one-time jobs. Particularly suitable for open-end discharge applications.

3:1 Design factor

### >> Lightweight and economical

<b>Tube</b>	Black EPDM
<b>Cover</b>	Black EPDM
<b>Reinforcement</b>	Multiple textile plies
<b>Temperature Range</b>	-20°F to +180°F (-29°C to +82°C)
<b>Branding</b>	PARKER SERIES 7306E WATER DISCHARGE HOSE 150 PSI MAX WP
<b>Brand Description</b>	Tape Brand - Blue stripe with black letters
<b>Compare to</b>	Goodyear Versiflo 125

**LENGTHS:** 100 ft.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Max. Rec. WP
7306E-1500	1½	38.1	2	1.80	45.7	45	150
7306E-2000	2	50.8	2	2.35	59.7	65	150
7306E-2500	2½	63.5	2	2.88	73.2	80	150
7306E-3000	3	76.2	2	3.45	87.6	110	150
7306E-4000	4	101.6	2	4.45	113.0	140	150

7306E

### Applications

- Irrigation
- Agriculture



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.