



7306M

## Applications

- Water Discharge

## DAY-FLO® Medium Duty Water Discharge Hose Series 7306M

Light, flexible and durable with 150 PSI working pressure in all sizes! This hose is the most versatile choice for many water discharge applications. The tube and cover are flexible EPDM rubber, which is resistant to weathering and to many light industrial and agricultural chemicals.

3:1 Design factor

### >> Versatile hose will handle many applications

<b>Tube</b>	Black EPDM
<b>Cover</b>	Black EPDM
<b>Reinforcement</b>	Textile tire cord plies
<b>Temperature Range</b>	-30°F to +212°F (-34°C to +100°C)
<b>Branding</b>	PARKER SERIES 7306M DAY-FLO MEDIUM WATER DISCHARGE HOSE 150 PSI MAX WP MADE IN USA
<b>Brand Description</b>	Embossed Brand
<b>Compare to</b>	Goodyear Plicord Water Discharge150; Gates Dolphin; Thermoid WD 150

**LENGTHS:** 100 ft. except 10 in. and 12 in. which are 50 ft.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Max. Rec. WP
7306M-5000	5	127.0	2	5.440	138.2	212	150
7306M-6000	6	152.4	2	6.488	164.8	284	150
7306M-8000	8	203.2	4	8.543	217.0	409	150
7306M-10000	10	254.0	4	10.535	267.6	522	150
7306M-12000	12	304.8	4	12.575	319.4	620	150



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.