



GULLY WASHER®

Standard Duty Lay Flat PVC Discharge Hose

Series 7541

A two-layer construction hose for water discharge in agriculture, mining, construction and other industrial applications. Strong, economical and lightweight hose that rolls up flat for easy storage. See Comparison Guide on page 161.

3:1 Design factor

>> Economical and lightweight

Tube	Blue Nitrile/PVC
Cover	Blue PVC
Reinforcement	Two-Spiral Polyester Plies, One Polyester Longitudinal Ply
Temperature Range	-10°F to +170°F (-23°C to +77°C)
Branding	None
Compare to	Gates Master-Flex 500; Goodyear Spiralflex Gray; Kanaflex 4501, 4502; Kuriyama NuFlo, VinylFlow; Petzetakis 11252; Sun-Flow SF-10, SF-15; Superflex DH

LENGTHS: 300 ft. bales.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	Nominal ID (in.)	Nominal ID (mm)	Reinf. Plies	Approx. Wall Thickness	Approx. Wt. per 100 Ft.	Max. Rec. WP
7541-1501	1½	40	3	0.051	14	65
7541-2001	2	53	3	0.051	17	60
7541-2501	2½	65	3	0.051	22	65
7541-3001	3	78	3	0.053	24	55
7541-4001	4	104	3	0.060	35	45
7541-6001	6	154	3	0.065	63	35
7541-8001	8	204	3	0.070	100	30

7541

Applications

- Construction
- Mining
- Agriculture
- Irrigation



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.