



GULLY WASHER® Medium Duty Lay Flat PVC Discharge Hose Series 7542

For medium duty water discharge applications in construction, agriculture, general industry and mining. Abrasion resistant construction provides long service life. Rolls up flat for easy storage. See Comparison Guide on page 161.

3:1 Design factor

>> Lays straight without kinking

Tube	Brick Red PVC/Nitrile
Cover	Brick Red PVC
Reinforcement	Two-Spiral Polyester Plies, One Polyester Longitudinal Ply
Temperature Range	-10°F to +170°F (-23°C to +77°C)
Branding	FLAME RESISTANT USMSHA 2G-60/1
Brand Description	Ink Brand - White letter color
Compare to	Goodyear Spiralflex Red; Jason 4510; Kuriyama Ironsides; Petzetakis 11298; Sun-Flow SF-30, SF-50

LENGTHS: 300 ft. bales.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7542

Part No.	Nominal ID (in.)	Nominal ID (mm)	Reinf. Plies	Approx. Wall Thickness	Approx. Wt. per 100 Ft.	Max. Rec. WP
7542-1501	1½	38.1	3	0.079	20	150
7542-2001	2	50.8	3	0.083	30	150
7542-2501	2½	63.5	3	0.091	40	150
7542-3001	3	76.2	3	0.091	52	150
7542-4001	4	101.6	3	0.102	74	150
7542-6001	6	152.4	3	0.114	125	120
7542-8001	8	203.2	3	0.120	189	100

Applications

- Construction
- Mining
- Agriculture
- Irrigation



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.