



GULLY WASHER® Heavy Duty Lay Flat PVC Discharge Hose Series 7545

For heavy duty water discharge service in applications such as agriculture, construction, industry and mining. Abrasion resistant PVC cover and Nitrile/PVC tube plus high adhesions between the layers provide for long service life. Rolls up flat for easy storage. MSHA brand. See Comparison Guide on page 161.

3:1 Design factor

>> Heavy duty construction for tough environments

Tube	Black PVC/Nitrile
Cover	Yellow PVC
Reinforcement	Two-Spiral Polyester Plies, One Polyester Longitudinal Ply
Temperature Range	-10°F to +170°F (-23°C to +77°C)
Branding	FLAME RESISTANT USMSHA 2G-60/1
Brand Description	Ink Brand - Black letter color
Compare to	Goodyear Spiralflex 2700, Brigade; Jason 4520; Petzetakis 11294; Sun-Flow SF-20.

LENGTHS: 300 ft. bales.

COUPLINGS: Available coupling option: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	Nominal ID (in.)	Nominal ID (mm)	Reinf. Plies	Approx. Wall Thickness	Approx. Wt. per 100 Ft.	Max. Rec. WP
7545-1501	1½	38.1	3	0.110	32	230
7545-2001	2	50.8	3	0.110	42	230
7545-2501	2½	63.5	3	0.122	56	230
7545-3001	3	76.2	3	0.122	68	175
7545-4001	4	101.6	3	0.134	101	160
7545-6001	6	152.4	3	0.157	185	150
7545-8001	8	203.2	3	0.157	268	150



7545

Applications

- Quarries
- Construction
- Mining
- Agriculture
- Irrigation



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.