



THORO-SPRAY® High Pressure Spray Hose – 800 PSI Series 7180

Designed for agricultural and residential high pressure spray applications. The tube will handle most pesticides, as well as liquid fertilizers. The cover is non-marking for safe use in residential areas.

4:1 Design factor


>> Non-marking cover

Tube	Black Nitrile
Cover	Green Nitrile/PVC
Reinforcement	Multiple textile braids
Temperature Range	-20° F to +180° F (-29°C to +82°C)
Branding	PARKER USA 7180 THORO-SPRAY® HOSE 800 PSI MAX WP
Brand Description	Ink Brand - Black letter color
Compare to	Goodyear Neptune 1500

LENGTHS: Random lengths on nominal 500 ft. reels, 5 piece maximum.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. Per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7180-252	¼	6.4	2	0.625	15.9	15	3.0	800
7180-382	⅜	9.5	2	0.750	19.1	20	4.0	800
7180-502	½	12.7	2	0.938	23.8	29	5.0	800
7180-752	¾	19.1	2	1.250	31.8	48	6.5	800



Applications

- Fertilizer
- Pesticide Sprayers