



SIAMEEZ®

Twin Welding Hose – Grade R

Series 7126 (Red – Acetylene Line Only)

TUBE AND COVER NOT OIL AND FLAME RESISTANT

This hose is recommended for portable or production line welding in factories, ships, construction work, etc. Meets or exceeds RMA and CGA (Compressed Gas Association) specifications for Type VD, Grade R welding hose. The tube is non-blooming. Minimum 4:1 Design factor

>> Rugged to withstand rough environments

Tube	Black EPDM
Cover	Vulcanized twin - Green (oxygen), Red (acetylene) EPDM
Reinforcement	Multiple textile spirals
Temp. Range	-20°F to +200°F (-29°C to +93°C)
Branding	PARKER 7126 WELDING WARNING! ACETYLENE ONLY 3/16 ID MAX WP 200 PSI RMA/CGA IP-7-99 STD DUTY GRADE R COUPLE WITH ONE INCH FERRULES MADE IN USA
Brand Description	Ink Brand - White letter color
Compare to	Goodyear Gemini Twinline Grade R; Thermoid Tuline Grade R

LENGTHS: 3/16" – 1/4" on 800 ft reel, 5/16" on 750 ft. reel, and 3/8" on 650 ft. reel. All reels are 90% 1 piece, 10% 2 pieces, 50 ft. min length (total footage is +0/-50 ft. of length indicated). Coupled assemblies also available.

COUPLINGS: Special right-hand or left-hand threaded brass inserts and crimp ferrules – not available from Parker. Couplings not sold or quoted separately.



7126

Applications

- Welding and Cutting Operations
- Factories, Shipyards, Construction Sites

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7126-191	3/16	4.8	2	0.438	11.1	13	2.0	200
7126-251	1/4	6.4	2	0.531	13.5	20	2.5	200
7126-311	5/16	7.9	2	0.594	15.1	25	3.0	200
7126-381	3/8	9.5	2	0.656	16.7	28	4.0	200



WARNING! Care should be taken to avoid gouging, dragging, abrading or otherwise damaging the hose cover, which may also lead to premature hose failure. Do not attempt to repair or re-couple hose assemblies; replace all assemblies that show signs of age or abuse. Refer to RMA IP-11-5, "Welding Hose, Precautions for the Selection and Use of".



WARNING! Grade R & RM for use with ACETYLENE GAS ONLY! DO NOT use with any other fuel gas. Bleed hoses when not in use for 30 minutes or longer. Couple with one inch ferrules only.