



Oxygen Charging Hose

Series 7293

Designed for lancing and scarfing applications in steel mills and foundries. This hose is made with high quality, flame resistant Neoprene rubber compounds that stand up to tough, oily environments. The green Neoprene cover is used to indicate color coding for oxygen. The tube is cleaned and the ends are capped at the factory.

4:1 Design factor

>> Designed to withstand tough environments

Tube	Black Neoprene
Cover	Green Neoprene
Reinforcement	Multiple textile plies
Temperature Range	-22°F to +176°F (-30°C to +80°C)
Branding	PARKER SERIES 7293 OXYGEN CHARGING 500 PSI MAX WP MADE IN USA 001
Brand Description	Embossed Brand
Compare to	Titan SS141 Oxygen Charging Hose

LENGTHS: 100 ft. all sizes. Lengths up to 200 ft. on quotation. Contact IHP Customer Service for details.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7293-0500	½	12.7	2	0.992	25.2	38	3.5	500
7293-0750	¾	19.1	2	1.276	32.4	54	3.5	500
7293-1000	1	25.4	2	1.528	38.8	68	4.5	500
7293-1250	1¼	31.8	2	1.930	49.0	108	5.0	500
7293-1500	1½	38.1	2	2.174	55.2	124	7.0	500
7293-2000	2	50.8	4	2.764	70.2	180	14.0	500

7293

Applications

- Lancing
- Scarfing