


Interlocking Clamps

Series 7692

PLATED MALLEABLE IRON

Service	For attaching high pressure coupling series 7611, 7615
Description	Plated malleable iron; 2, 4 and 6 bolt configuration
Manufacturer	Dixon Valve & Coupling
Torque Specifications	Contact Dixon Valve & Coupling



Hose ID (in.)	From Hose OD (in.)	From Hose OD (mm)	To Hose OD (in.)	To Hose OD (mm)	Bolts	Part Number
1/2	9/16	14.3	21/32	16.7	2	-251
3/8	21/32	16.7	13/16	20.6	2	-381
1/2	13/16	20.6	115/16	23.8	2	-501
1/2	15/16	23.8	11/16	27.0	2	-502
1/2	11/16	27.0	13/16	30.2	2	-503
3/4	13/16	30.2	15/16	33.3	2	-751
3/4	15/16	33.3	11/2	38.1	2	-752
3/4	11/2	38.1	111/16	42.9	2	-753
1	117/32	38.9	123/32	43.7	4	-1001
1	111/16	42.9	127/32	46.8	4	-1002
1	17/8	47.6	21/16	52.4	4	-1003
1 1/4	21/16	52.4	21/4	57.2	4	-1251
1 1/4	125/32	45.2	23/32	53.2	4	-1252
1 1/2	23/32	53.2	29/32	57.9	4	-1501
1 1/2	21/4	57.2	27/16	61.9	4	-1502
1 1/2	215/32	62.7	223/32	69.1	4	-1503
2	21/2	63.5	225/32	70.6	4	-2001
2	23/4	69.9	31/16	77.8	4	-2002
2	33/32	78.6	37/16	87.3	4	-2003
2 1/2	31/2	88.9	315/16	100.0	4	-2501
3	313/16	96.8	43/16	106.4	4	-3001
3	41/16	103.2	47/16	112.7	4	-3002
4	47/8	123.8	55/16	134.9	6	-4001
4	51/8	130.2	63/16	157.2	6	-4002