

## Dimensions of Seamless and Welded Steel Pipe

ASA—B36.10 and B36.19

Nominal Pipe Size (in.)	Outside Diameter (in.)	10	20	30	Standard	40	60	Extra Strong	80	100	120	140	150	XX Strong
1/8	0.405	-	-	-	0.068	0.068	-	0.095	0.095	-	-	-	-	-
1/4	0.540	-	-	-	0.088	0.088	-	0.119	0.119	-	-	-	-	-
3/8	0.675	-	-	-	0.091	0.091	-	0.126	0.126	-	-	-	-	-
1/2	0.840	-	-	-	0.109	0.109	-	0.147	0.147	-	-	-	0.188	0.294
3/4	1.050	-	-	-	0.113	0.113	-	0.154	0.154	-	-	-	0.219	0.308
1	1.315	-	-	-	0.133	0.133	-	0.179	0.179	-	-	-	0.250	0.358
1 1/4	1.660	-	-	-	0.140	0.140	-	0.191	0.191	-	-	-	0.250	0.382
1 1/2	1.900	-	-	-	0.145	0.145	-	0.200	0.200	-	-	-	0.281	0.400
2	2.375	-	-	-	0.154	0.154	-	0.218	0.218	-	-	-	0.344	0.436
2 1/2	2.875	-	-	-	0.203	0.203	-	0.276	0.276	-	-	-	0.375	0.552
3	3.50	-	-	-	0.216	0.216	-	0.300	0.300	-	-	-	0.438	0.600
3 1/2	4.00	-	-	-	0.226	0.226	-	0.318	0.318	-	-	-	-	-
4	4.50	-	-	-	0.237	0.237	-	0.337	0.337	-	0.438	-	0.531	0.674
5	5.563	-	-	-	0.258	0.258	-	0.375	0.375	-	0.500	-	0.625	0.750
6	6.625	-	-	-	0.280	0.280	-	0.432	0.432	-	0.562	-	0.719	0.864
8	8.625	-	0.250	0.277	0.322	0.322	0.406	0.500	0.500	0.594	0.719	0.812	0.906	0.873
14 O.D.	14.00	0.250	0.312	0.375	0.375	0.438	0.594	0.500	0.750	0.938	1.094	1.250	1.406	-
16 O.D.	16.00	0.250	0.312	0.375	0.375	0.500	0.656	0.500	0.844	1.031	1.219	1.438	1.594	-
18 O.D.	18.00	0.250	0.312	0.438	0.375	0.562	0.750	0.500	0.938	1.156	1.375	1.562	1.781	-
20 O.D.	20.00	0.250	0.375	0.500	0.375	0.594	0.812	0.500	1.031	1.281	1.500	1.750	1.969	-
22 O.D.	22.00	0.250	0.375	0.500	0.375	-	0.875	0.500	1.125	1.375	1.625	1.875	2.125	-
24 O.D.	24.00	0.250	0.375	0.562	0.375	0.688	0.969	0.500	1.218	1.531	1.812	2.062	2.344	-
26 O.D.	26.00	0.312	0.500	-	0.375	-	-	0.500	-	-	-	-	-	-
28 O.D.	28.00	0.312	0.500	0.625	.0375	-	-	0.500	-	-	-	-	-	-
30 O.D.	30.00	0.312	0.500	0.625	0.375	-	-	0.500	-	-	-	-	-	-
32 O.D.	32.00	0.312	0.500	0.625	0.375	0.688	-	0.500	-	-	-	-	-	-
34 O.D.	34.00	0.312	0.500	0.625	0.375	0.688	-	0.500	-	-	-	-	-	-
36 O.D.	36.00	0.312	0.500	0.625	0.375	0.750	-	0.500	-	-	-	-	-	-
42 O.D.	42.00	-	-	-	0.375	-	-	0.500	-	-	-	-	-	-