

## 1035A - Power Cleaning 1200 to 1500 PSI



Part Number	I. D.		Max. O. D.		Max. Working Pressure		Min. Bend Radius		Weight		Crimp Fitting		80C Crimp Die
	inch	mm	inch	mm	wpsi	MPa	inch	mm	lbs/ft	kg/m	series	pg	crimp die
#													
hose	inch	mm	inch	mm	wpsi	MPa	inch	mm	lbs/ft	kg/m	series	pg	crimp die
1035A-4	1/4	6	0.52	13	1500	10.3	5/8	15.9	.084	.12	55	53-77	P04
1035A-6	3/8	10	0.65	17	1200	8.3	7/8	22.2	.100	.15	55	53-77	P06

\*HBR (Hose Bend Restrictor) suggested for carpet cleaning applications. See hose guard in Hose Accessories section.

**Min. Burst Pressure is 4x Max. Working Pressure**

**Tube:** Special PFX Compound

**Reinforcement:** Fiber

**Cover:** Urethane, perforated

**Cover Color:** Blue

**Temperature Range:** -25°F to +212°F

-32°C to +100°C

**Vacuum Rating:** 28 inch Hg

**(Delta) Working Length @ Rated WPSI:** ±2% Max.

**Applications/Markets:**

Water applications

Carpet cleaning

**Note:** No chlorinated solvents should be used

**Special Features:**

Optional colors

Non-marring

## 1035HT - Power Cleaning 1500 to 1750 PSI



Part Number	I. D.		Max. O. D.		Max. Working Pressure		Min. Bend Radius		Weight		Crimp Fitting		80C Crimp Die
	inch	mm	inch	mm	wpsi	MPa	inch	mm	lbs/ft	kg/m	series	pg	crimp die
#													
hose	inch	mm	inch	mm	wpsi	MPa	inch	mm	lbs/ft	kg/m	series	pg	crimp die
1035HT-3	3/16	5	0.43	11	2000	15.8	3/4	19.1	.043	.06	55	53-77	P03
1035HT-4	1/4	6	0.51	13	1750	12.1	1-1/2	38.1	.057	.08	55	53-77	P04
1035HT-6	3/8	10	0.65	17	1500	10.4	2	50.8	.086	.13	55	53-77	P06

\*HBR (Hose Bend Restrictor) suggested for carpet cleaning applications. See hose guard in Hose Accessories section.

**Min. Burst Pressure is 4x Max. Working Pressure**

**Tube:** Special PFX Compound

**Reinforcement:** Fiber

**Cover:** Urethane, perforated

**Cover Color:** Yellow

**Temperature Range:** -40°F to +230°F

-40°C to +110°C

**Vacuum Rating:** 28 inch Hg

**(Delta) Working Length @ Rated WPSI:** ±2% Max.

**Applications/Markets:**

Water applications

Carpet cleaning

**Note:** No chlorinated solvents should be used

**Special Features:**

Optional colors

Non-marring

Broad temperature range

**Note:** The above hose(s) are not intended for use in static discharge applications; i.e., airless paint spray.