

# 61 Series — ISO A Interchange

*Featuring...Snap-tite quality with superior pressure and flow characteristics over the competition*



- Interchangeable with other manufacturers offering ISO Series A couplings.
- Dimensional & performance requirements conform to ISO 7241-1 Series A
- 4:1 Safety Factor
- Proven ball-lock mechanism provides positive connection
- Poppet style shut-off
- High strength steel construction
- Zinc yellow dichromate plating for corrosion resistance
- Choice of seal materials to handle a variety of fluids
- Sizes 1/4" – 1"

*Snap-tite's 61 Series is designed to conform to the dimensional and performance requirements of ISO 7241-1 Series A, which details the testing, performance and dimensions of the nipple. This is to enable interchangeability with couplings produced by other manufacturers who meet the same standard. Snap-tite's 61 Series features superior working pressures, flow characteristics and safety factors, making the 61 Series the premier ISO Series A interchange.*

## PRESSURE RATINGS

SIZE	MAXIMUM WORKING		MINIMUM BURST		MAXIMUM CONNECT BY HAND	
	PSI	BAR	PSI	BAR	PSI	BAR
1/4"	4,600	317	18,400	1269	150	10
3/8"	4,600	317	18,400	1269	150	10
1/2"	4,000	276	16,000	1103	100	7
3/4"	4,000	276	16,000	1103	50	3
1"	3,000	207	12,000	828	40	3