HOW TO ORDER							
PART NO. 61		61 C	6- 6	F			
Series	Coupling Half	Coupling Size	End Fitting Size	End Fitting Type	Seals	Options	
61	C Coupler N Nipple	4 = 1/4" 6 = 3/8" 8 = 1/2" 12 = 3/4" 16 = 1"	4 = 1/4" 6 = 3/8" 8 = 1/2" 10 = 5/8" 12 = 3/4" 16 = 1"	F Female NPTF RP Female British Parallel BS2779 EF* Female SAE	Std. seal is Buna V = Viton E = Ethylene Propylene Rubber M = MIL-H-5606	SL Sleeve Lock	

*SAE Threads: 1/4" is supplied with 3/8" SAE (4-6EF) only

3/8" is supplied with 1/2" SAE (6-8EF) only

1/2" can be supplied with 5/8" SAE (8-10EF) if required

All others are size for size (8-8EF, 12-12EF, 16-16EF)

ACCESSORIES

		DUST PLUG	DUST CAP
Γ	1/4"	61PDP-4	61PDC-4
	3/8"	PDP-8	PDC-8
	1/2"	61PDP-8	PDC-12
ſ	3/4"	61PDP-12	61PDC-12
ſ	1"	61PDP-16	61PDC-16

! WARNING !

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND/OR PROPERTY DAMAGE.

This document and other information from Snap-tite, Inc., its subsidiaries and authorized distributors, provides product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operation conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Snap-tite, Inc. and its subsidiaries at any time without notice.

