SS200 BREWERS HOSE - CHLOROBUTYL TUBE

Capped ends available upon request.

Microbe and bacteria resistant tube.

Meets FDA, USDA, 3A, and PMO sanitary requirements.



- Brewery discharge hose designed specifically for transferring non-oily foods and liquids in wineries and breweries.
- Special construction provides excellent flexibility and handling ease for in-plant use.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that is microbe resistant and will not impart taste or odor.
- Abrasion resistant cover offers excellent ozone protection.

Tube: Extruded white Chlorobutyl.

Reinforcement: Textile.

Cover: Orange specially compounded EPDM.

Temperature: -40° to +225°F.

I.D.	0.D.	REINFORCEMENT	WORKING Pressure PSI	WEIGHT LB/FT
11/2"	23/8"	4 plies	350	1.33
2"	3"	6 plies	350	1.91
2 ¹ / ₂ "	3 ¹ / ₂ "	6 plies	350	2.32
3"	4 ¹ /8"	6 plies	350	3.05
4"	5 ¹ /8"	6 plies	350	3.87

SS231 FOOD GRADE DISCHARGE HOSE - NATURAL RUBBER TUBE

Meets FDA and USDA sanitary requirements.



- Low pressure sanitary discharge hose designed to handle dry food and beverage products. Excellent for in-plant transfer.
- Lightweight construction provides superior flexibility for handling ease.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.

Tube: Extruded Natural Rubber. **Reinforcement:** Textile with internal static wire.

Cover: Gray specially compounded Natural Rubber.

Temperature: -40° to +150°F.

I.D.	0.D.	REINFORCEMENT	WORKING Pressure PSI	WEIGHT LB/FT
2"	2 ²⁷ / ₃₂ "	2 plies	200	1.60
2 ¹ / ₂ "	311/32"	2 plies	200	1.92
3"	3 ²⁷ /32"	2 plies	140	2.23
4"	4 ²⁷ / ₃₂ "	2 plies	120	2.88
6"	6 ²⁷ /32"	2 plies	110	4.27