

Preformed Clamping Systems



BAND-IT Center Punch clamps are locked with a standard conical punch, ensuring a strong, powerful lock for reliable clamping. Both 201 stainless steel and galvanized carbon steel CP clamps are manufactured with 201 stainless steel buckles to provide maximum locking strength.

Center Punch clamps can be installed with BAND-IT's T300 or S038 hand tools. The new, electric-powered IT9000 is the ideal solution to high-speed production requirements.



The Universal Clamp is a single wrap, preformed, smooth I.D. clamp that can be fastened with either a Tie-Lok or Ultra-Lok termination. Use the A920 or IT1000 for Tie-Lok. For Ultra-Lok, use the A940 or IT3000 tools.



Worm Gear Clamps
A quality screwdriver type clamp with mechanical interlock eliminating spot weld for greater strength and protection from corrosion. The extra wide band, 9/16", provides more compression area. Band made of 301 S.S.

Clamp	Clamp I.D.		Band Thickness		Band Width		Range Clamp Diameter			
	In	(mm)	In	(mm)	In	(mm)	Inches Min	Inches Max	mm Min	mm Max
<i>BAND-IT Jr.</i> 201 S.S. or GCS	1 1/2	38.1	.030	.76	5/8	15.9				
	1 3/4	44.5	.030	.76	5/8	15.9				
	2	50.8	.030	.76	5/8	15.9				
	2 1/4	57.2	.030	.76	5/8	15.9				
	2 1/2	63.5	.030	.76	5/8	15.9				
	2	50.8	.030	.76	3/4	19.1				
	2 1/2	63.5	.030	.76	3/4	19.1				
	2 3/4	69.9	.030	.76	3/4	19.1				
	3	76.2	.030	.76	3/4	19.1				
	3 1/2	88.9	.030	.76	3/4	19.1				
	4	101.6	.030	.76	3/4	19.1				
	4 1/2	114.3	.030	.76	3/4	19.1				
	5	127.0	.030	.76	3/4	19.1				
	5 1/4	133.4	.030	.76	3/4	19.1				
	6	152.4	.030	.76	3/4	19.1				
	7	177.8	.030	.76	3/4	19.1				
8	203.2	.030	.76	3/4	19.1					
<i>Center Punch</i> 201 S.S. or GCS All buckles 201 S.S.	1 3/16	20	.025	.64	3/8	9.5				
	1 3/8	35	.025	.64	3/8	9.5				
	1	25	.025	.64	5/8	16				
	1 1/4	32	.025	.64	5/8	16				
	1 1/2	38	.025	.64	5/8	16				
	1 3/4	44	.025	.64	5/8	16				
	2	51	.025	.64	5/8	16				
	2 1/4	57	.025	.64	5/8	16				
	2 1/2	64	.025	.64	5/8	16				
	2 3/4	70	.025	.64	5/8	16				
	3	76	.025	.64	5/8	16				
	3 1/2	89	.025	.64	5/8	16				
	4	102	.025	.64	5/8	16				
	4 1/2	114	.025	.64	5/8	16				
	5	127	.025	.64	5/8	16				
	6	152	.025	.64	5/8	16				
7	178	.025	.64	5/8	16					
8	203	.025	.64	5/8	16					
<i>Universal Clamp</i> 201 S.S.	1	25	.015	.38	1/4	6.35				
	1 1/2	38	.015	.38	1/4	6.35				
	2	51	.015	.38	1/4	6.35				
	2 1/2	64	.015	.38	1/4	6.35				
	3	76	.015	.38	1/4	6.35				
	3 1/2	89	.015	.38	1/4	6.35				
	4	102	.015	.38	1/4	6.35				
	4 1/2	114	.015	.38	1/4	6.35				
<i>Worm Gear Clamps</i> 301 S.S.			.023	.6	9/16	14	3/8	7/8	9	22
			.023	.6	9/16	14	1/16	1	11	25
			.023	.6	9/16	14	1/2	1 1/8	12	28
			.023	.6	9/16	14	1/2	1 1/4	12	32
			.023	.6	9/16	14	3/4	1 1/2	19	38
			.023	.6	9/16	14	7/8	1 3/4	22	45
			.023	.6	9/16	14	1 1/8	2	28	51
			.023	.6	9/16	14	1 3/8	2 1/4	35	57
			.023	.6	9/16	14	1 5/8	2 1/2	41	64
			.023	.6	9/16	14	1 7/8	2 3/4	48	70
			.023	.6	9/16	14	2 1/8	3	54	76
			.023	.6	9/16	14	2 5/16	3 1/4	58	83
			.023	.6	9/16	14	2 5/8	3 1/2	67	89
			.023	.6	9/16	14	2 7/8	3 3/4	73	95
			.023	.6	9/16	14	3 1/8	4	79	102
			.023	.6	9/16	14	3 1/2	4 1/2	89	114
			.023	.6	9/16	14	4	5	102	127
			.023	.6	9/16	14	4 1/2	5 1/2	114	140
		.023	.6	9/16	14	5 1/8	6	130	152	
		.023	.6	9/16	14	6 1/8	7	155	178	