

EW399 DOCK / O.S. & D. HOSE - 250 PSI

Custom Made Hose Product



- Heavy duty, high pressure, suction and discharge dock hose excellent for petro-chemical applications.
- Rugged all-purpose cover is chemical, oil, scuff, gouge, and ozone resistant.
- Meets all U.S.C.G. requirements for Dock hose.

Tube: FKM Fluoroelastomer.
Reinforcement: High strength tire cord with steel wire helix.
Cover: Oil resistant synthetic rubber.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
4"	5 ¹ / ₄ "	24"	250	5.50	Full
6"	7 ⁵ / ₁₆ "	36"	250	8.50	Full
8"	9 ¹ / ₂ "	48"	250	14.80	Full

EW460RB MOLTEN SULPHUR DOCK HOSE

Custom Made Hose Product



- Heavy duty modified rough bore construction designed to handle Molten Sulphur up to 300°F. degrees.
- Heat and chemical resistant high grade EPDM tube and cover.

Tube: Black high grade EPDM.
Reinforcement: High strength tire cord with steel wire helix.
Cover: EPDM.
Temperature: -40° to +300°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
6"	8"	42"	200	12.00	Full
8"	10 ¹ / ₄ "	54"	200	20.00	Full
10"	12 ¹ / ₄ "	66"	200	28.00	Full

EWC439 FLEX BARGE DOCK HOSE - 225 PSI

Custom Made Hose Product



- Heavy duty, all purpose oil suction and discharge hose suitable for up to 60% aromatics.
- Corrugated construction provides superior flexibility and kink resistance.
- Dual wire helix reinforcement provides full vacuum capabilities.
- High grade multi-purpose cover is oil, ozone, abrasion, and gouge resistant.

Tube: Nitrile.
Reinforcement: High strength tire cord with dual steel wire helix.
Cover: Oil resistant synthetic rubber.
Temperature: -40° to +180° F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
4"	5"	18"	225	4.30	Full
6"	7 ¹ / ₄ "	27"	225	8.20	Full
8"	9 ¹³ / ₃₂ "	36"	225	12.30	Full
10"	11 ²³ / ₃₂ "	45"	225	21.01	Full
12"	13 ²⁹ / ₃₂ "	54"	225	27.06	Full