

ES937 ELEPHANT TRUNK HOSE - 1/8" SBR TUBE

- Designed exclusively for gravity flow and low pressure discharge of cement and other abrasive materials.
- Lightweight construction provides excellent flexibility for handling ease.
- Premium quality tube and cover resists cuts and abrasions.

Tube: 1/8" SBR.
Reinforcement: High strength tire cord.
Cover: SBR.
Temperature: -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
6"	6 ¹⁷ / ₃₂ "	2 plies	65	2.90
6 ⁵ / ₈ "	7 ⁵ / ₃₂ "	2 plies	60	3.10
7"	7 ¹⁷ / ₃₂ "	2 plies	60	3.30
7 ¹ / ₂ "	8 ¹ / ₃₂ "	2 plies	55	3.60
8"	8 ¹⁷ / ₃₂ "	2 plies	50	3.80
8 ⁵ / ₈ "	9 ⁵ / ₃₂ "	2 plies	45	4.20
10"	10 ¹⁷ / ₃₂ "	2 plies	45	4.90
10 ³ / ₄ "	11 ⁹ / ₃₂ "	2 plies	40	5.20
12"	12 ¹⁷ / ₃₂ "	2 plies	40	5.80
12 ³ / ₄ "	13 ⁹ / ₃₂ "	2 plies	40	6.20
14"	14 ¹⁷ / ₃₂ "	2 plies	35	6.80
16"	16 ¹⁷ / ₃₂ "	2 plies	30	7.70
18"	18 ¹⁷ / ₃₂ "	2 plies	30	8.70
20"	20 ¹⁷ / ₃₂ "	2 plies	25	9.60
22"	22 ¹⁷ / ₃₂ "	2 plies	20	10.60
24"	24 ¹⁷ / ₃₂ "	2 plies	20	11.50
30"	30 ¹⁹ / ₃₂ "	2 plies	20	14.00

Custom Made Hose Product



EW336 EXACTA PIPE MATERIAL SUCTION HOSE - 1/4" NATURAL RUBBER TUBE

- All-weather general purpose suction and discharge hose designed to handle highly abrasive material.
- Natural rubber tube provides excellent rebound, durability, and abrasion resistance.

Tube: 1/4" Natural Rubber.
Reinforcement: High strength tire cord with steel wire helix.
Cover: SBR.
Temperature: -40° to +150°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
4"	5 ¹ / ₈ "	24"	100	4.50	Full
5"	6 ¹ / ₈ "	30"	100	5.80	Full
6"	7 ¹ / ₈ "	36"	100	7.10	Full
6 ⁵ / ₈ "	7 ³ / ₄ "	40"	100	7.80	Full
8"	9 ¹ / ₄ "	48"	100	11.70	Full
8 ⁵ / ₈ "	9 ⁷ / ₈ "	52"	100	12.50	Full
10"	11 ³ / ₈ "	60"	100	15.00	Full
10 ³ / ₄ "	12 ¹ / ₄ "	65"	100	20.20	Full
12"	13 ¹ / ₂ "	72"	100	22.50	Full
12 ³ / ₄ "	14 ¹ / ₄ "	77"	100	23.80	Full
14"	15 ¹ / ₂ "	84"	100	27.50	Full

Custom Made Hose Product

Refer to SW336 (page 48) for additional sizes and working pressures.
 Various tube thicknesses and corrugated construction available upon request.

