EW360 HOT AIR BLOWER HOSE

Custom Made Hose Product

Refer to SW360 (page 48) for additional sizes and working pressures.

Corrugated and 4 ply constructions available upon request.



- High temperature, ultra-durable hose for transferring hot air.
- Superior grade tube will withstand temperatures up to 300°F.
- Heavy duty EPDM cover is heat and ozone resistant.

Reinforcement: High strength tire cord with steel wire helix.

Cover: Heat resistant EPDM. Temperature: -40° to +300°F.

I.D.	0.D.	BEND RADIUS	WORKING Pressure PSI	WEIGHT LB/FT	VACUUM
6"	6 ⁷ /8"	36"	100	5.70	Full
6 ⁵ /8"	7 ¹ /2"	42"	100	6.30	Full
8"	87/8"	48"	75	8.00	Full
8 ⁵ /8"	9 ⁵ /8"	52"	75	10.00	Full
10"	11"	60"	65	12.50	Full
103/4"	11 ⁷ /8"	65"	60	15.00	Full
12"	13 ¹ /8"	72"	55	17.50	Full
123/4"	13 ⁷ /8"	77"	50	18.50	Full
14"	15 ¹ /8"	84"	50	21.50	Full

EWC334 CORRUGATED MATERIAL HANDLING - 1/2" NATURAL RUBBER TUBE

Custom Made Hose Product

Various tube thicknesses available upon request.



- · All-weather corrugated material suction hose designed to handle abrasive materials.
- Natural rubber tube provides excellent rebound, durability, and abrasion resistance.
- · All weather cover resists cuts, gouging and ozone attack.

Tube: 1/8" Natural Rubber.

Reinforcement: High strength textile with dual wire helix.

Cover: Corrugated SBR. Temperature: -40° to +150°F.

I.D.	0.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
6"	6 ⁷ /8"	29"	135	5.60	Full
6 ⁵ /8"	7 ¹ /2"	32"	125	6.40	Full
8"	8 ⁷ /8"	38"	100	8.00	Full
8 ⁵ /8"	9 9/16"	42"	95	8.80	Full
10"	11"	48"	85	11.60	Full
10 ³ / ₄ "	11³/4"	52"	75	12.40	Full
12"	13 ¹ /8"	58"	65	16.50	Full
12³/ ₄ "	13 ⁷ /8"	62"	65	17.50	Full