

**EWC888 INDUSTRIAL VACUUM HOSE - 1/8" NATURAL RUBBER TUBE**

Custom Made Hose Product



- Industrial material handling hose for vacuum service and low pressure applications.
- Lightweight corrugated design provides superior flexibility for handling ease.
- Dual wire reinforcement provides full vacuum capabilities.

**Tube:** 1/8" Natural Rubber.  
**Reinforcement:** High strength tire cord with dual wire helix.  
**Cover:** Corrugated SBR.  
**Temperature:** -40° to +150°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
5"	5 3/4"	20"	75	4.00	Full
6"	6 3/4"	24"	65	4.60	Full
8"	8 7/8"	36"	50	6.80	Full
10"	10 7/8"	48"	40	10.30	Full

**SS135 DRY CEMENT DISCHARGE HOSE - 1/8" SBR TUBE**

Static conductive tube.



- Low pressure material transfer hose designed for discharge service of dry cement and powdered abrasive materials.
- Lightweight construction provides superior flexibility without sacrificing quality.
- Premium grade cover resists cuts, scuffs, and ozone attack.

**Tube:** 1/8" Extruded SBR.  
**Reinforcement:** Textile.  
**Cover:** SBR.  
**Temperature:** -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
4"	4 1/2"	2 plies	65	1.49
4 1/2"	5"	2 plies	65	1.67
5"	5 1/2"	2 plies	65	1.84
6"	6 1/2"	2 plies	65	2.24