

SS242 PETROLEUM DISCHARGE HOSE

- Petroleum discharge hose designed for on-shore service of diesel fuels and other petroleum products.
- Durable all-weather cover is oil and ozone resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile with internal static wire.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
2"	2 ¹¹ / ₁₆ "	2 plies	200	1.21
3"	3 ¹¹ / ₁₆ "	2 plies	150	1.70
4"	4 ¹¹ / ₁₆ "	2 plies	125	2.26
6"	6 ¹¹ / ₁₆ "	2 plies	100	3.30

SS243 with tan cover available upon request.



SS254 OIL AND GAS HOSE

- Lightweight oil and gasoline discharge hose used for transferring petroleum products.
- Rugged cover is oil, abrasion and chemical resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
6"	6 ²⁷ / ₃₂ "	4 plies	150	4.10
8"	8 ²⁷ / ₃₂ "	4 plies	150	5.52



SW303 PETROLEUM SUCTION HOSE

- Premium grade petroleum suction and discharge hose suitable for 60% aromatics.
- Excellent tank wagon hose where flexibility is a must.
- Dual wire helix construction provides full vacuum capabilities.
- Cover is oil, abrasion and ozone resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +180°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 ¹ / ₄ "	1 ¹¹ / ₁₆ "	4"	200	.51	Full
1 ¹ / ₂ "	2"	5"	200	.64	Full
2"	2 ¹ / ₂ "	6"	200	.95	Full
2 ¹ / ₂ "	3"	8"	150	1.32	Full
3"	3 ¹ / ₂ "	12"	150	1.68	Full
4"	4 ⁵ / ₈ "	18"	150	2.63	Full

